



SPECIFICATION CONTROL DRAWING



D3683-X INSERT



DART P/N	THREAD SIZE	"D" MAX	"HD" ±0.015	"HH"	"L" ±0.015	POSSIBLE SUPPLIERS
D3683-1	#10-32	Ø0.296	Ø0.415	0.030	0.475	AVIBANK MFG INC P/N: ALS7-1032-130 ALS4-1032-130 AKS7-1032-130 AKS4-1032-130 ATLAS ENGINEERING: AELS-1032-130 SPAENAUR INC: 215-074
D3683-3	1/4-28	Ø0.390	Ø0.500	0.030	0.580	AVIBANK MFG INC P/N: ALS7-428-165 ALS4-428-165 AKS7-428-165 AKS4-428-165 ATLAS ENGINEERING: AELS-428-165 SPAENAUR INC: 215-076

NOTES:

- 1) MATERIAL: C-1010 OR C-1008 STEEL
- 2) FINISH: CAD PLATED PER QQ-P-416 TYPE II (GOLD) CLASS 2 WITH CLEAR PROTECTIVE COATING OR ZINC YELLOW PLATED PER ASTM-B633, FE/ZN 8, TYPE II WITH CLEAR PROTECTIVE COATING (OPTIONAL)
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: N/A
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: N/A
- 8) THREADS: UNIFIED, CLASS 2B PER ASME B1.1
- 9) A CERTIFICATE OF CONFORMITY IS REQUIRED FROM THE MANUFACTURER TO VERIFY MATERIAL, FINISH, AND THREADS ARE PER THIS DWG

B	ADDED P/N D3683-3	RF	09.03.30
A	NEW ISSUE	DC	07.11.21
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE USA, INC. PORT HADLOCK, WA	
DRAWN	RF		
CHECKED		DRAWING NO.	REV. B
MFG. APPR.		D3683	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		INSERT	NTS
DATE	09.03.30	COPYRIGHT © 2007 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

RELEASED
09/07/15